

DELPHION

No active trail

Log Out: [Work Files](#) [Saved Searches](#) [My Account](#)[Search](#) [QuickNumber](#) [Bookman](#) [Advanced](#) [Derwent](#) [Help](#)

The Delphion Integrated View

Get Now: <input checked="" type="checkbox"/> PDF File History Other Choices	Tools: Add to Work File Create new Work File Add
View: INPADOC Jump to: Top	Go to: Derwent <input checked="" type="checkbox"/> Email this to a friend

JP2002161623A2: EXTERNAL-FACING BACKING STRUCTURE AND EXTERNAL-FACING BACKING CONSTRUCTION METHOD

Derwent Title: Exterior foundation structure in building, has wall to support cement board layer whose outer surface is coated with cement mortar [Derwent Record]

Country: JP Japan

Kind: A2 Document Laid open to Public Inspection 1

Inventor: HIROSHIGE RYOICHI,

ITO YOSHIMITSU,

Assignee: MITSUI HOME CO LTD

MITSUBISHI RAYON CO LTD

News, Profiles, Stocks and More about this company

Published / Filed: 2002-06-04 / 2000-11-27

Application Number: JP2000000359862


IPC Code: IPC-7: E04F 1302; E04B 1/70; E04B 2/56;

Priority Number: 2000-11-27 JP2000000359862

Abstract:

PROBLEM TO BE SOLVED: To propose a quite new semi-drying and semi-wet type external facing backing structure in which not only design properties, maintainability and reproducibility but also workability and quality characteristics are improved.

SOLUTION: The external-facing backing structure contains a cement board layer 3 supported on the outside of an exterior-wall skeleton layer 1 and a cement mortar layer 4 applied on the external side face of the cement board layer 3. The cement board

View
Image

1 page

layer 3 is constituted by laying and arranging a plurality of cement boards 3a, 3a and the like in a plane shape, joints 3b are filled with cement mortar, and the cement board layer 3 is covered with a glass fiber net 4a from the outsides of the joints. Both surfaces of the cement board layer 3 are reinforced by the glass fiber nets, and irregularities are formed to the external side face of the cement board layer 3. A ventilation space layer 2 is formed between the exterior-wall skeleton layer 1 and the cement board layer 3.

COPYRIGHT: (C)2002, JPO

None

DERABS G2002-523534

 Family:
 Other Abstract
Info:



[Nominate this for the Gallery...](#)

THOMSON
★

Copyright © 1997-2006 The Thomson Corporation
[Subscriptions](#) | [Webinars](#) | [Privacy](#) | [Terms & Conditions](#) | [Site Map](#) | [Contact Us](#) | [Help](#)